



Chain Bag ST 2012







Operation and use

- Bag designed for the protected transport of lock-chain-combinations
- Flexible mounting with non-slip velcro straps or screws at the bottle holder device
- 2 mm strong Neoprene to keep the content cool or warm
 Strengthened innerplate for easy mounting

Tip

• This bag can also be used for the transport of standard 0,5l bottles

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
ST 2012 Chain Bag	58496 1		200 g	24 x 10 x 9 cm	1	

EaZy KF



Operation and use

- Transport of U-shackle locks
- Mounting on round frames with a diameter of 28 36 mm
- Screws in two lengths included Plastic bracket for mounting with rubber inlays for best hold
- Index marks on the bracket to simplify subsequent mountings Comfortable one-hand-operation
 Very quick mounting
- Patented design



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
EaZy KF	45342 7			for Abus No. 64/61/54/51/47	1
Shackle Clamp 11mm	45344 1	11 mm		for ABUS No.61/64 EaZy KF	1
Shackle Clamp 12mm	45347 2	12 mm		for ABUS No. 47 EaZy KF	1
Shackle Clamp 13mm	45343 4	13 mm		for ABUS No. 54 EaZy KF	1
Shackle Clamp 13mm	45346 5	13 mm		for ABUS No. 51 EaZy KF	1

TexKF Twin





Operation and use

- Transport of U-shackle locks
- Mounting on round and non-round frame profile with a diameter of 21-80 mm
 Flexible textile sleeve for mounting
 Mounting within the frame or at the side possible
- Simple and time saving mounting



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
TexKF Twin	23264 0			for ABUS No. 54, 51	1



TexKF Mini



.

Operation and use

- Transport mostly cable, coil cable and Steel-O-Flex locks Mounting on round and non-round frame profiles with a diameter of 21-80 mm
- Flexible textile sleeve for mounting
 Mounting within the frame or at the side possible
- Simple and time saving mounting



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
TexKF Mini	23265 7			for ABUS No. 64, 896, 895,	1
				894, 860, 800, 1460, 1450,	
				1440	

USH 501



Operation and use

Transport of 501 lock
Mounting on round frames with a diameter of 15-35 mm



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
USH 501	58914 0		1380 g	for uGrip Plus 501	1	

USH 54/51/47/46





Operation and use

- Transport of U-shackle locks
- Transport of U-snackle locks
 Mounting on round frames with a diameter of 15 35 mm
 Plastic bracket for mounting
 Comfortable one-hand-operation
 Mounting within the frame or at the side possible

Ref. No	EAN	Version	Weight	Technical	P.U.*	
	4003318			details		
USH 54	23762 1			for ABUS No. 54HB	1	
USH 51	36462 4			for ABUS No. 51HB	1	
USH 46/47	12861 5			for ABUS No. 47HB/46HB	1	



GH 50



Operation and use Transport of U-shackle locks
Mounting on the side of the rack
Plastic bracket for mounting

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
GH50	00904 4			for ABUS No. 64, 51, 47, 46	1

UGH 02





Operation and use

- Transport of Steel-0-Flex and other locks
 Mounting on the rack stays with a diameter of 5-16.5 mm
 Universal solution for all common racks
 Simple and time saving mounting

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
UGH 02	26624 9			for ABUS No. 1050, 1025, 1000, 950, 900, 9000,	1	
				8220, 8200		

Shackle Clamp







Operation and use

Accessory for the transport in a TUBUS LOCC U-shackle lock carrier, TexKF Twin or RBKF Twin



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
Shackle Clamp	27348 3	13 mm		for ABUS No. 54HB	1	
Shackle Clamp 13mm	25998 2	13 mm		for ABUS No. 51HB	1	
Shackle Clamp 12mm	25604 2	12 mm		for ABUS No. 46, 47HB	1	
Shackle Clamp 11mm	25580 9	11 mm		for ABUS No. 64, 61HB	1	



Ivera RBU



Operation and use

- Transport of chain, cable and Steel-o-flex locks of the Ivera series
 Mounting on round and non-round frame profiles with a diameter of 15-45 mm or
- with the practical bracket on the frame Easy mounting with a metal sleeve or LL bracket



QuickSnap RBU





Operation and use

- Transport of cable and Steel-O-Flex locks •
- Mounting on round and non-round frame profiles with a diameter of 15-45 mm
- Flexible metal sleeve for mounting
 Mounting within the frame or at the side possible
- Simple and time saving mounting

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
QuickSnap RBU	31487 2			for ABUS No. 860, 870	6

RBKF Mini



Operation and use

- Transport of coil cables
 Mounting on round and non-round frame profiles with a diameter of 25-45 mm
 Flexible metal sleeve for mounting
 Mounting within the frame or at the side possible



Ref. No	EAN	Version	Weight	Technical	P.U.*
	4003318			details	
RBKF Mini	12434 1			for ABUS No. 885, 64/120	6



QuickSnap



Operation and use

- Transport of cable and Steel-O-Flex locks
 Mounting on all common seat post bolts (diameter 5-8 mm)
 Simple mounting

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
QuickSnap	31488 9			for ABUS No. 860/85, 870	1

KF




Operation and use

- Transport of cable, coil cable and Steel-O-Flex locks
 Mounting on all common seat post bolts (diameter 5-8 mm)
 Simple mounting

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
KF	12433 4			for ABUS No. 896, 895,	6
				894, 885, 875, 1350, 1355,	
				1340, 1440, 1450, 1460	

URB (universal frame bracket)





Operation and use


Accessory for transporting locks with the LL carrier
 Enables transporting the lock on the seat post or on the frame (diameter 25-35 mm)

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
URB	23312 8			25 - 35 mm	12



Saddle - KF





Transport of locks under the saddle
Simple and time saving mounting



 Besides numerous locks, this carrier can also be used for several saddle bags of the ABUS bag portfolio



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
Saddle - KF	04306 2			for ABUS Coil Cables	6	

Seat Post Clamp



Operation and use • Transport of cable locks with LL bracket

Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*
Seat Post Clamp	51710 5		35 g	Ø 31.8 mm	1
Seat Post Clamp	51711 2		35 g	Ø 34.9 mm	1

Bordo 6000 ECOLUTION™ Bracket





Operation and use • Transport of Bordo 6000



Ref. No	EAN 4003318	Version	Weight	Technical details	P.U.*	
Bordo 6000 bracket	59160 0	replacement bracket			1	

